


BE-H型



性能表

型 式	吐出 口径	回転速度 min ⁻¹	標準吸込状態空気量(m ³ /min)および所要動力(kW)															
			10kPa (1020mmAq)		20kPa (2040mmAq)		30kPa (3060mmAq)		40kPa (4080mmAq)		50kPa (5100mmAq)		60kPa (6120mmAq)		70kPa (7140mmAq)		80kPa (8160mmAq)	
			m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW
BE50E	50A (2B)	2200	1.40	0.7	1.31	1.0	1.22	1.2	1.13	1.5	1.04	1.9						
		2500	1.66	0.8	1.57	1.1	1.48	1.4	1.39	1.8	1.30	2.2						
		2750	1.87	0.9	1.78	1.2	1.69	1.6	1.60	2.0	1.51	2.5						
		3050	2.12	1.0	2.03	1.4	1.94	1.8	1.85	2.3	1.76	2.7						
		3300	2.34	1.0	2.25	1.5	2.16	1.9	2.07	2.4	1.98	2.9						
		3600	2.59	1.1	2.50	1.6	2.41	2.1	2.32	2.6	2.23	3.2						
BE65H	65A (2½)	2100	2.35	1.0	2.31	1.4	2.27	1.9	2.24	2.4	2.20	3.0	2.16	3.5	2.12	4.1	2.08	4.6
		2350	2.70	1.1	2.66	1.6	2.62	2.2	2.59	2.7	2.55	3.3	2.51	3.9	2.47	4.5	2.43	5.1
		2450	2.84	1.1	2.80	1.7	2.76	2.3	2.73	2.9	2.69	3.5	2.65	4.1	2.61	4.7	2.57	5.4
		2600	3.05	1.2	3.01	1.8	2.97	2.4	2.94	3.0	2.90	3.7	2.86	4.4	2.82	5.1	2.78	5.8
		2750	3.26	1.3	3.22	2.0	3.18	2.6	3.15	3.2	3.11	3.9	3.07	4.6	3.03	5.3	2.99	6.0
		2900	3.47	1.4	3.43	2.1	3.39	2.7	3.36	3.4	3.32	4.2	3.28	4.9	3.24	5.7	3.20	6.4
		3250	3.96	1.5	3.92	2.3	3.88	3.0	3.85	3.8	3.81	4.7	3.77	5.5	3.73	6.3		
BE80H	80A (3B)	2100	3.81	1.4	3.73	2.2	3.65	2.9	3.57	3.7	3.49	4.5	3.41	5.4	3.33	6.2	3.25	7.1
		2350	4.25	1.6	4.17	2.4	4.09	3.2	4.01	4.1	3.93	5.0	3.85	5.9	3.77	6.7	3.69	7.6
		2450	4.47	1.6	4.39	2.5	4.31	3.4	4.23	4.3	4.15	5.2	4.07	6.2	3.99	7.1	3.91	8.0
		2600	4.80	1.7	4.72	2.6	4.64	3.6	4.56	4.5	4.48	5.6	4.40	6.6	4.32	7.6	4.24	8.6
		2750	5.13	1.9	5.05	2.8	4.97	3.8	4.89	4.9	4.81	6.0	4.73	7.1	4.65	8.1	4.57	9.2
		2900	5.46	2.0	5.38	3.0	5.30	4.1	5.22	5.2	5.14	6.4	5.06	7.5	4.98	8.7	4.90	9.8
		3250	6.23	2.1	6.15	3.4	6.07	4.6	5.99	5.9	5.91	7.2	5.83	8.6	5.75	9.9		
BE100H	100A (4B)	2050	5.79	2.1	5.64	3.2	5.50	4.3	5.35	5.4	5.21	6.6	5.06	7.8	4.91	9.0	4.76	10.2
		2150	6.12	2.2	5.97	3.3	5.83	4.5	5.68	5.7	5.54	6.9	5.39	8.1	5.24	9.4	5.09	10.7
		2300	6.60	2.4	6.45	3.6	6.31	4.8	6.16	6.1	6.02	7.3	5.87	8.7	5.72	10.0	5.57	11.4
		2400	6.92	2.5	6.77	3.7	6.63	5.0	6.48	6.3	6.34	7.6	6.19	9.0	6.04	10.4	5.89	11.8
		2700	7.88	3.0	7.73	4.4	7.59	5.8	7.44	7.3	7.30	8.8	7.15	10.3	7.00	11.9	6.85	13.4
		2900	8.52	3.2	8.37	4.8	8.23	6.4	8.08	8.0	7.94	9.6	7.79	11.3	7.64	13.0	7.49	14.7
		3050	9.00	3.4	8.85	5.1	8.71	6.7	8.56	8.5	8.42	10.2	8.27	12.1	8.12	13.9		
BE125H	125A (5B)	1750	8.8	2.8	8.7	4.6	8.6	6.5	8.5	8.3	8.4	10.2	8.3	12.0	8.2	13.8	8.1	15.6
		1950	10.0	3.0	9.9	5.1	9.8	7.2	9.7	9.3	9.6	11.4	9.5	13.4	9.4	15.5	9.3	17.5
		2150	11.2	3.4	11.1	5.7	11.0	8.0	10.9	10.3	10.8	12.6	10.7	14.9	10.6	17.2	10.5	19.4
		2400	12.7	3.9	12.6	6.5	12.5	9.0	12.4	11.6	12.3	14.2	12.2	16.8	12.1	19.4	12.0	22.0
		2700	14.5	4.6	14.4	7.4	14.3	10.4	14.2	13.2	14.1	16.2	14.0	19.1	13.9	22.1	13.8	25.0
		2900	15.7	5.0	15.6	8.0	15.5	11.1	15.4	14.3	15.3	17.5	15.2	20.6	15.1	23.8	15.0	27.0
		3050	16.6	5.3	16.5	8.4	16.4	11.7	16.3	15.1	16.2	18.4	16.1	21.8	16.0	25.1	15.9	28.5
BE150H	150A (6B)	1550	17.5	4.9	17.2	8.4	16.9	11.9	16.6	15.3	16.3	18.7	16.0	22.1	15.7	25.5	15.4	28.9
		1700	19.4	5.6	19.1	9.4	18.8	13.2	18.5	16.9	18.2	20.7	17.9	24.4	17.6	28.1	17.3	31.8
		1800	20.7	6.0	20.4	10.0	20.1	14.0	19.8	18.0	19.5	22.0	19.2	25.9	18.9	29.8		
		1950	22.6	6.7	22.3	11.0	22.0	15.3	21.7	19.6	21.4	23.9	21.1	28.2	20.8	32.4		
		2100	24.5	7.3	24.2	11.9	23.9	16.6	23.6	21.2	23.3	25.9	23.0	30.5	22.7	35.1		
		2250	26.5	8.0	26.2	13.0	25.9	18.0	25.6	22.9	25.3	27.8	25.0	32.8	24.7	37.8		
		2550	30.3	9.2	30.0	14.8	29.7	20.5	29.4	26.2	29.1	31.8	28.8	37.5	28.5	43.2		

BE-H型



性能表

型 式	吐出 口径	回転速度 min ⁻¹	標準吸込状態空気量 (m ³ /min) および所要動力 (kW)															
			10kPa (1020mmAq)		20kPa (2040mmAq)		30kPa (3060mmAq)		40kPa (4080mmAq)		50kPa (5100mmAq)		60kPa (6120mmAq)		70kPa (7140mmAq)		80kPa (8160mmAq)	
			m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW
BE200H	200A (8B)	1450	33.0	9.1	32.8	15.2	31.6	21.5	30.9	28.0	30.2	34.7	29.5	41.7	28.8	48.7	28.1	55.7
		1550	35.6	9.9	35.4	16.3	34.2	23.0	33.5	30.0	32.8	37.2	32.1	44.7	31.4	52.2	30.7	59.8
		1700	39.4	11.2	39.2	18.1	38.0	25.4	37.3	33.0	36.6	40.9	35.9	49.3	35.2	57.6	34.5	65.9
		1800	42.0	12.1	41.8	19.4	40.6	27.0	39.9	35.0	39.2	43.5	38.5	52.4	37.8	61.3		
		1950	45.8	13.6	45.6	21.4	44.4	29.5	43.7	38.3	43.0	47.4	42.3	57.1	41.6	66.9		
		2050	48.3	14.7	48.1	22.8	46.9	31.2	46.2	40.6	45.5	50.2	44.8	60.4	44.1	70.6		
		2150	50.9	15.9	50.7	24.3	49.5	33.1	48.8	42.9	48.1	53.1	47.4	63.8	46.7	74.5		
BE250H	250A (10B)	1250	52.4	17.9	51.7	27.2	51.0	36.6	50.3	46.6	49.6	56.1	48.9	66.1	48.2	76.1	47.5	86.1
		1350	57.0	19.5	56.3	29.6	55.6	39.8	54.9	50.6	54.2	60.9	53.5	71.7	52.8	82.5		
		1450	61.6	21.1	60.9	32.0	60.2	43.1	59.5	54.7	58.8	65.7	58.1	77.3	57.4	88.9		
		1600	68.6	23.5	67.9	35.5	67.2	48.0	66.5	60.9	65.8	73.0	65.1	85.9	64.4	98.8		
		1700	73.2	25.0	72.5	37.8	71.8	51.3	71.1	65.0	70.4	77.8	69.7	91.5	69.0	105		
		1800	77.8	26.6	77.1	40.2	76.4	54.6	75.7	69.0	75.0	82.6	74.3	97.2	73.6	112		
		1950	84.8	29.0	84.1	43.8	83.4	59.5	82.7	75.1	82.0	89.9	81.3	106	80.6	122		
BE300H	300A (12B)	1300	73.5	20.3	72.5	35.5	71.5	50.7	70.5	65.8	69.5	81.0	68.5	96.1				
		1350	76.8	21.4	75.8	37.2	74.8	52.9	73.8	68.6	72.8	84.4	71.8	100				
		1450	83.3	23.5	82.3	40.5	81.3	57.4	80.3	74.2	79.3	91.2	78.3	108				
		1550	89.9	26.1	88.9	44.1	87.9	62.2	86.9	80.2	85.9	98.2	84.9	116				
		1650	96.4	28.6	95.4	47.9	94.4	67.1	93.4	86.4	92.4	106	91.4	125				
		1750	103	31.4	102	51.8	101	72.2	100	92.6	99.0	113	98.0	133				
BE350H	350A (14B)	1200	109	27.5	107	48.2	106	68.8	104	89.5	103	110	101	131				
		1300	119	31.0	117	53.6	116	76.2	114	98.8	113	121	111	144				
		1350	124	32.8	122	56.3	121	80.0	119	103	118	127	116	151				
		1450	134	36.3	132	61.8	131	87.4	129	113	128	138	126	164				
		1550	144	39.8	142	67.2	141	94.9	139	122	138	150	136	177				
		1650	154	43.3	152	72.6	151	102	149	132	148	161	146	190				
BE400H	400A (16B)	900	161	42	159	73	157	104	155	135	153	166	151	196				
		1050	191	51	189	87	187	123	185	159	183	195	181	232				
		1150	211	57	209	97	207	136	205	176	203	215	201	256				
		1250	230	64	228	107	226	150	224	193	222	236						
		1300	240	68	238	112	236	157	234	201	232	246						
		1350	250	72	248	118	246	165	244	211								

※型式 50Hz 仕様: 5BE〇〇H
60Hz 仕様: 6BE〇〇H

部は、ハウジング、ギャカパー水冷式(冷却水量15~25L/min)

※吐出圧力 61kPa 以上の場合、高圧仕様対応品となります。
標準仕様品(60kPa 以下)は、高圧仕様では使用できません。
詳細は、お問い合わせ下さい。