


性能表

型 式	吐 出 口 径	回転速度	標準吸込状態空気量 (m³/min) および所要動力 (kW)											
			10kPa (1020mmAq)		20kPa (2040mmAq)		30kPa (3060mmAq)		40kPa (4080mmAq)		50kPa (5100mmAq)		60kPa (6120mmAq)	
		min ⁻¹	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW
BH50	50A (2B)	1150	1.50	0.7	1.33	1.0	1.18	1.4	1.04	1.7	0.91	2.0	0.79	2.4
		1250	1.68	0.8	1.51	1.2	1.36	1.5	1.22	1.8	1.09	2.2	0.97	2.6
		1350	1.86	0.9	1.69	1.3	1.54	1.7	1.40	2.0	1.27	2.4	1.15	2.8
		1400	1.95	0.9	1.78	1.3	1.63	1.7	1.49	2.1	1.36	2.5	1.24	2.9
		1550	2.22	1.0	2.05	1.5	1.90	1.9	1.76	2.3	1.63	2.7	1.51	3.2
		1700	2.49	1.1	2.32	1.6	2.17	2.1	2.03	2.5	1.90	3.0	1.78	3.5
BH65	65A (2½B)	1150	1.95	0.8	1.67	1.2	1.45	1.7	1.27	2.1	1.14	2.6		
		1250	2.20	0.9	1.92	1.3	1.70	1.9	1.52	2.4	1.39	2.9	1.29	3.5
		1400	2.58	1.0	2.30	1.5	2.08	2.1	1.90	2.7	1.77	3.3	1.67	3.9
		1550	2.95	1.2	2.67	1.7	2.45	2.3	2.27	3.0	2.14	3.7	2.04	4.4
		1700	3.33	1.3	3.05	1.9	2.83	2.6	2.65	3.3	2.52	4.0	2.42	4.8
BH80	80A (3B)	1150	3.19	1.2	3.03	1.9	2.86	2.6	2.73	3.3	2.63	4.0	2.52	4.7
		1250	3.55	1.3	3.39	2.0	3.22	2.8	3.09	3.6	2.99	4.4	2.88	5.2
		1400	4.09	1.5	3.93	2.3	3.76	3.2	3.63	4.0	3.53	4.9	3.42	5.8
		1550	4.63	1.7	4.47	2.6	4.30	3.6	4.17	4.5	4.07	5.5	3.96	6.5
		1700	5.17	1.9	5.01	2.9	4.84	4.0	4.71	5.0	4.61	6.1	4.50	7.2
BH100	100A (4B)	1100	4.34	1.8	4.16	2.6	4.00	3.4	3.85	4.3	3.71	5.3	3.57	6.3
		1300	5.32	2.2	5.15	3.0	4.99	4.0	4.84	5.1	4.70	6.3	4.56	7.4
		1450	6.04	2.4	5.87	3.4	5.71	4.5	5.56	5.7	5.42	7.0	5.29	8.3
		1550	6.52	2.6	6.35	3.6	6.19	4.8	6.04	6.1	5.90	7.5	5.77	8.9
		1750	7.45	3.1	7.28	4.2	7.12	5.6	6.97	7.0	6.83	8.6	6.70	10.1
		1950	8.36	3.4	8.19	4.7	8.03	6.2	7.88	7.9	7.74	9.6	7.61	11.4
BH125	125A (5B)	1100	6.65	2.4	6.45	3.7	6.25	5.0	6.05	6.4	5.85	7.9	5.65	9.5
		1300	8.19	2.9	7.99	4.3	7.79	5.9	7.59	7.6	7.39	9.4	7.19	11.2
		1450	9.35	3.2	9.15	4.8	8.95	6.5	8.75	8.5	8.55	10.5	8.35	12.5
		1550	10.1	3.4	9.92	5.1	9.72	7.0	9.52	9.1	9.32	11.2	9.12	13.4
		1750	11.7	4.0	11.5	5.9	11.3	8.1	11.1	10.4	10.9	12.8	10.7	15.3
		1950	13.2	4.5	13.0	6.7	12.8	9.1	12.6	11.7	12.4	14.4	12.2	17.2
BH125A	125A (5B)	1100	9.1	2.8	8.7	4.7	8.4	6.6	8.2	8.5	8.0	10.6	7.8	12.7
		1300	11.2	3.4	10.8	5.7	10.5	8.0	10.3	10.3	10.1	12.7	9.9	15.2
		1450	12.7	3.9	12.3	6.4	12.0	8.9	11.8	11.5	11.6	14.2	11.4	17.0
		1550	13.7	4.3	13.3	7.0	13.0	9.7	12.8	12.5	12.6	15.3	12.4	18.3
		1750	15.8	5.2	15.4	8.2	15.1	11.2	14.9	14.3	14.7	17.6	14.5	21.0
		1950	17.9	6.1	17.5	9.4	17.2	12.8	17.0	16.3	16.8	19.9	16.6	23.7
BH150	150A (6B)	900	14.0	4.4	13.6	6.8	13.3	9.4	13.0	12.2	12.7	15.1	12.4	18.1
		1050	16.8	5.3	16.4	8.3	16.1	11.3	15.8	14.5	15.5	17.9	15.2	21.5
		1150	18.6	5.8	18.2	9.1	17.9	12.4	17.6	15.9	17.3	19.6	17.0	23.5
		1250	20.5	6.6	20.1	10.0	19.8	13.7	19.5	17.5	19.2	21.5	18.9	25.7
		1400	23.2	7.6	22.8	11.5	22.5	15.6	22.2	19.9	21.9	24.4	21.6	29.1
		1550	26.0	8.8	25.6	13.1	25.3	17.6	25.0	22.4	24.7	27.5	24.4	32.8



性能表

型 式	吐 出 口 径	回転速度	標準吸込状態空気量(m³/min)および所要動力(kW)											
			10kPa (1020mmAq)		20kPa (2040mmAq)		30kPa (3060mmAq)		40kPa (4080mmAq)		50kPa (5100mmAq)		60kPa (6120mmAq)	
		min ⁻¹	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW
BH150A	150A (6B)	900	20.0	7.0	18.7	10.6	17.5	14.1	16.5	18.2	15.5	22.3	14.7	26.4
		1050	23.8	8.2	22.5	12.4	21.4	16.5	20.4	21.3	19.2	26.0	18.6	30.8
		1150	26.3	9.0	25.0	13.6	23.8	18.0	22.8	23.3	21.8	28.5	21.0	33.8
		1250	28.9	9.8	27.6	14.8	26.4	19.6	25.4	25.3	24.4	31.0	23.6	36.7
		1400	32.8	10.9	31.5	16.5	30.3	21.9	29.3	28.4	28.3	34.7	27.5	41.1
		1550	36.7	12.1	35.4	18.3	34.2	24.3	33.2	31.4	32.2	38.4	31.4	45.5
BH200	200A (8B)	900	25.2	8.2	24.0	12.2	22.8	16.2	21.7	20.2	20.6	24.1	19.6	28.8
		1050	29.2	9.2	28.0	14.0	26.8	19.0	25.7	23.9	24.6	28.8	23.6	34.3
		1150	32.2	9.8	31.0	15.4	29.8	21.0	28.7	26.7	27.7	32.3	26.7	38.5
		1250	35.0	10.4	33.9	16.8	32.8	23.2	31.8	29.5	30.8	35.9	29.7	43.1
		1350	38.1	11.1	37.0	18.2	35.9	25.3	34.8	32.4	33.8	40.0	32.8	47.8
		1450	41.2	11.9	40.0	19.7	38.8	27.5	37.8	35.4	36.7	43.0	35.9	52.5
BH200A	200A (8B)	900	31.6	10.7	29.9	16.1	28.3	22.4	27.0	28.9	25.6	35.1	24.5	42.8
		1050	37.6	12.5	35.9	18.8	34.2	26.1	32.9	33.7	31.5	41.0	30.7	50.0
		1150	41.5	13.7	39.8	20.5	38.2	28.6	36.9	37.0	35.4	44.9	34.3	54.7
		1250	45.6	14.9	43.8	22.3	42.3	31.1	41.0	40.2	39.6	48.8	38.5	59.5
		1350	49.5	16.1	47.9	24.1	46.3	33.6	45.0	43.4	43.5	52.7	42.5	64.2
		1450	53.5	17.3	51.8	25.9	50.2	36.1	48.9	46.6	47.5	56.6	46.4	69.0
BH250	250A (10B)	800	34.7	9.5	34.1	16.4	33.5	23.3	32.9	30.2	32.3	37.1	31.7	44.0
		900	39.8	11.3	39.2	19.1	38.6	26.8	38.0	34.6	37.4	42.3	36.8	50.1
		1000	44.8	13.1	44.2	21.7	43.6	30.3	43.0	39.0	42.4	47.6	41.8	56.2
		1100	49.9	14.9	49.3	24.4	48.7	33.9	48.1	43.3	47.5	52.8	46.9	62.3
		1200	54.9	16.7	54.3	27.0	53.7	37.4	53.1	47.7	52.5	58.1	51.9	68.4
		1300	60.0	18.5	59.4	29.7	58.8	40.9	58.2	52.1	57.6	63.3	57.0	74.5
		1400	65.0	20.3	64.4	32.4	63.8	44.4	63.2	56.5	62.6	68.5	62.0	80.6
BH250A	250A (10B)	800	49.1	24.8	47.8	33.5	46.8	42.2	45.9	50.8	45.2	59.5	44.5	68.1
		900	55.7	26.0	54.5	35.7	53.4	45.4	52.5	55.2	51.8	64.9	51.2	74.6
		1000	62.4	27.1	61.1	37.9	60.0	48.7	59.1	59.5	58.4	70.3	57.8	81.1
		1100	69.0	28.1	67.7	40.0	66.6	51.9	65.8	63.8	65.0	75.7	64.4	87.6
		1200	75.6	29.3	74.3	42.2	73.2	55.2	72.4	68.1	71.6	81.1	71.0	94.1
		1300	82.2	30.4	80.9	44.4	79.9	58.4	79.0	72.5	78.3	86.5	77.6	101
BH300	300A (12B)	800	51.6	16.5	48.6	26.5	46.6	37.0	44.6	46.5	42.6	55.5	40.6	68.0
		1000	67.0	20.6	64.0	33.1	62.0	46.3	60.0	58.0	58.6	69.4	56.0	85.0
		1200	82.3	24.8	79.3	39.8	77.3	55.5	75.3	69.8	73.3	83.3	71.3	102
		1400	97.7	28.9	94.7	46.4	92.7	64.8	90.7	81.4	88.7	97.1	86.7	119
		1500	105.3	30.9	102.3	49.7	100.3	69.4	98.3	87.2	96.3	104	94.3	128
BH350	350A (14B)	800	95.2	31.7	92.2	46.8	90.2	63.4	88.2	80.9	86.2	100	85.2	120
		900	108	35.7	105	52.6	103	71.3	101	91.0	99.1	113	98.1	135
		1000	121	39.6	118	58.5	116	79.2	114	101	112	125	111	150
		1100	134	43.6	131	64.3	129	87.2	127	111	125	138	124	165
		1200	147	47.5	144	70.2	142	95.1	140	121	138	150	137	180