


BS-G型(ガス用ブロワ)



性能表

型 式	吐 出 口 径	回転速度 min ⁻¹	標準吸込状態空気量 (m ³ /min) および所要動力 (kW)											
			10kPa (1020mmAq)		20kPa (2040mmAq)		30kPa (3060mmAq)		40kPa (4080mmAq)		50kPa (5100mmAq)		60kPa (6120mmAq)	
			m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW
BS32GS	32A (1½B)	1600	0.44	0.41	0.34	0.54	0.23	0.68						
		1750	0.54	0.47	0.44	0.62	0.34	0.78						
		1900	0.64	0.55	0.54	0.71	0.44	0.90	0.35	1.1				
		2050	0.74	0.63	0.64	0.82	0.54	1.0	0.45	1.3				
		2200	0.85	0.72	0.75	0.94	0.65	1.2	0.56	1.4	0.47	1.7		
BS40GE	40A (1½B)	1200	0.94	0.64	0.83	0.83	0.75	1.0	0.69	1.3				
		1300	1.04	0.71	0.93	0.92	0.85	1.1	0.79	1.4	0.73	1.6		
		1400	1.14	0.78	1.03	1.0	0.94	1.2	0.89	1.5	0.83	1.7	0.78	1.9
		1500	1.24	0.86	1.13	1.1	1.04	1.3	0.98	1.6	0.92	1.9	0.87	2.2
		1600	1.34	0.94	1.23	1.2	1.14	1.4	1.08	1.7	1.02	2.0	0.97	2.4
BS50GE	50A (2B)	1000	1.30	0.9	1.15	1.2	1.03	1.5	0.94	1.8				
		1150	1.61	1.0	1.45	1.5	1.33	1.8	1.23	2.3	1.13	2.8		
		1250	1.81	1.2	1.65	1.7	1.52	2.1	1.43	2.5	1.32	3.0	1.28	3.5
		1400	2.11	1.4	1.94	1.8	1.81	2.3	1.72	2.8	1.61	3.3	1.56	4.0
		1500	2.31	1.6	2.14	2.1	2.01	2.6	1.91	3.1	1.80	3.6	1.75	4.1
BS65GE	65A (2½B)	1000	1.89	1.4	1.74	1.7	1.64	2.1	1.56	2.5	1.47	2.8	1.39	3.3
		1150	2.24	1.6	2.09	2.0	1.98	2.4	1.90	2.9	1.81	3.4	1.71	3.9
		1250	2.47	1.8	2.32	2.2	2.21	2.7	2.12	3.2	2.03	3.7	1.93	4.2
		1350	2.70	1.9	2.54	2.4	2.44	2.9	2.35	3.5	2.25	4.0	2.15	4.6
		1450	2.94	2.1	2.77	2.6	2.66	3.1	2.57	3.7	2.47	4.3	2.37	5.0
BS80GE	80A (3B)	1550	3.17	2.2	3.00	2.8	2.89	3.3	2.79	3.9	2.69	4.5	2.58	5.3
		1000	3.28	1.9	3.11	2.5	3.02	3.3	2.91	4.0	2.86	4.7	2.66	5.5
		1100	3.69	2.1	3.52	2.8	3.42	3.6	3.31	4.4	3.26	5.3	3.05	6.2
		1200	4.10	2.3	3.92	3.0	3.83	4.0	3.71	4.8	3.66	5.8	3.45	6.8
		1300	4.52	2.6	4.33	3.6	4.23	4.4	4.12	5.3	4.06	6.3	3.84	7.3
BS100GE	100A (4B)	1350	4.73	2.7	4.54	3.7	4.44	4.6	4.32	5.5	4.26	6.5	4.04	7.5
		1450	5.14	2.9	4.95	4.0	4.84	4.9	4.72	6.0	4.66	7.2	4.43	8.0
		1550	5.55	3.5	5.36	4.5	5.25	5.4	5.12	6.6	5.06	7.8	4.83	8.9
		900	5.05	2.5	4.64	3.5	4.36	4.4	4.12	5.5	3.89	6.8	3.72	7.7
		1000	5.93	2.9	5.35	4.1	5.02	5.1	4.80	6.3	4.58	7.6	4.39	8.8
BS125GE	125A (5B)	1100	6.59	3.3	6.06	4.7	5.73	5.8	5.48	7.2	5.28	8.3	5.07	10.0
		1200	7.48	3.7	6.77	5.3	6.34	6.5	6.16	8.0	5.97	9.1	5.75	11.1
		1300	8.15	4.1	7.48	5.7	7.05	7.0	6.85	8.7	6.67	10.1	6.43	12.1
		1400	8.82	4.6	8.19	6.0	7.75	7.5	7.49	9.4	7.26	11.0	7.10	13.0
		1450	9.27	4.8	8.62	6.2	8.15	7.8	7.82	9.8	7.59	11.5	7.44	13.5
BS150GE	150A (6B)	800	10.3	4.4	10.0	6.1	9.7	8.3	9.4	10.5	9.2	13.2	8.9	16.1
		900	11.7	4.8	11.5	6.8	11.1	9.3	10.8	11.6	10.6	14.6	10.3	17.6
		1000	13.2	5.3	12.9	7.5	12.6	10.3	12.3	12.9	12.0	16.0	11.7	19.2
		1100	14.7	5.9	14.4	8.3	14.0	11.3	13.7	14.3	13.4	17.5	13.1	20.9
		1200	16.1	6.4	15.8	9.2	15.4	12.2	15.2	15.6	14.9	19.1	14.5	22.8
BS200GE	200A (8B)	1300	17.6	7.0	17.3	10.1	16.9	13.6	16.6	17.4	16.3	21.2	15.9	25.1
		1350	18.3	7.4	18.0	10.6	17.6	14.3	17.3	18.2	17.0	22.2	16.6	26.3
		800	17.0	6.9	16.5	9.6	16.1	12.4	15.8	15.4	15.5	18.4	14.9	21.4
		900	19.3	8.0	18.8	11.1	18.4	14.5	18.1	18.0	17.8	21.5	17.2	25.0
		1000	21.7	9.1	21.1	12.8	20.8	16.5	20.4	20.6	20.1	24.5	19.4	28.7
BS200DGS	200A (8B)	1050	22.9	9.8	22.3	13.6	21.9	17.5	21.5	21.8	21.2	26.0	20.6	30.4
		1100	24.1	10.3	23.5	14.4	23.1	18.7	22.7	23.1	22.4	27.7	21.7	32.2
		1150	25.3	10.9	24.6	15.1	24.2	19.7	23.8	24.4	23.5	29.2	22.8	34.0
		1200	26.4	11.4	25.8	16.0	25.4	20.7	25.0	25.6	24.7	30.7	24.0	35.8
		1250	27.6	12.0	27.0	16.8	26.6	21.7	26.1	27.0	25.8	32.2	25.1	37.6
BS250GE	250A (10B)	700	28.5	11.9	27.8	15.7	27.1	20.0	26.7	25.0	26.4	30.6	26.1	36.5
		750	30.8	13.0	30.0	17.0	29.4	21.7	29.0	27.2	28.7	33.2	28.4	39.7
		800	33.1	14.0	32.3	18.4	31.7	23.5	31.3	29.4	31.0	35.9	30.7	42.8
		850	35.4	15.0	34.6	19.8	34.0	25.2	33.6	31.5	33.3	38.5	33.0	46.0
		900	37.6	16.0	36.9	21.1	36.3	26.9	35.9	33.7	35.6	41.1	35.3	49.1
BS250DGS	250A (10B)	950	39.9	17.1	39.2	22.4	38.6	28.6	38.2	35.8	37.9	43.8	37.6	52.2
		1000	42.2	18.1	41.5	23.7	40.9	30.3	40.5	37.9	40.2	46.4	39.9	55.4
		1050	44.5	19.1	43.8	25.1	43.2	32.0	42.8	40.1	42.5	49.0	42.2	58.5
		1100	46.8	20.4	46.1	26.9	45.5	34.3	45.1	42.9	44.8	52.5	44.5	62.7
		700	29.3	9.0	27.7	14.5	26.4	20.1	25.4	25.8	24.5	31.7	23.6	37.6
BS300GS	300A (12B)	750	31.6	9.6	30.0	15.6	28.7	21.5	27.7	27.6	26.8	33.9	25.9	40.3
		800	34.0	10.2	32.4	16.6	31.1	22.9	30.1	29.6	29.2	36.1	28.3	43.0
		850	36.4	10.9	34.8	17.6	33.5	24.4	32.5	31.4	31.6	38.4	30.7	45.7
		900	38.7	11.6	37.1	18.6	35.8	25.8	34.8	33.3	33.9	40.6	33.0	48.3
		950	41.1	12.2	39.5	19.7	38.2	27.2	37.2	35.1	36.3	43.0	35.4	51.0
BS300GE	300A (12B)	1000	43.5	12.9	41.9	20.7	40.6	28.7	39.6	36.9	38.7	45.2	37.8	53.7
		1050	45.8	13.5	44.2	21.7	42.9	30.1	41.9	38.8	41.0	47.4	40.1	56.4
		1100	48.2	14.1	46.6	22.8	45.3	31.5	44.3	40.6	43.4	49.7	42.5	59.1
		700	48.1	15.4	46.3	24.1	44.5	32.8	44.0	41.5	43.2	50.4	42.3	59.4
		750	52.0	16.7	50.2	26.0	48.4	35.5	48.0	44.9	47.1	54.4	46.2	64.3
BS300DGS	300A (12B)	800	55.9	17.9	54.1	28.1	52.3	38.1	51.9	48.3	51.1	58.6	50.2	69.1
		850	59.8	19.1	58.1	30.0	56.3	40.9	55.9	51.6	55.0	62.6	54.1	74.0
		900	63.7	20.4	62.0	31.9	60.2	43.5	59.8	55.1	59.0	66.7	58.1	78.7
		950	67.6	21.7	65.9	33.9	64.1	46.1	63.7	58.4	62.9	70.8	62.0	83.6
		1000	71.5	22.9	69.8	35.9	68.1	48.9	67.7	61.9	66.9	74.9	66.0	88.4
BS300GS	300A (12B)	1050	75.4	24.2	73.7	37.8	72.0	51.5	71.6	65.2	70.8	79.0	69.9	93.3
		700	61.2	20.2	58.9	31.6	56.9	43.2	55.1	54.8	53.4	67.4	51.9	80.4
		750	66.1	21.6	63.8	34.0	61.8	46.2	60.0	58.8	58.3	72.3	56.8	86.1
		800	71.1	23.2	68.8	36.2	66.8	49.4	65.0	62.6	63.3	77.1	61.8	91.9
		850	76.0	24.6	73.7	38.4	71.7	52.4	69.9	66.6	68.2	81.9	66.7	97.6
BS300GS	300A (12B)	900	81.0	26.0	78.7	40.7	76.7	55.5	74.9	70.5	73.2	86.7	71.7	103
		950	85.9	27.5	83.6	43.0	81.6	58.6	79.8	74.5	78.1	91.6	76.6	109
		1000	90.9	28.9	88.6	45.3	86.6	61.7	84.8	78.3	83.1	96.3	81.6	115