


BSW型 (水冷式高圧ブロワ)



性能表

型式	吐出口径	回転速度 min ⁻¹	標準吸込状態空気量 (m ³ /min) および所要動力 (kW)										冷却水量 ℓ/min
			60kPa (6120mmAq)		70kPa (7140mmAq)		80kPa (8160mmAq)		90kPa (9180mmAq)		100kPa (10200mmAq)		
			m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	
BSW65E	65A (2½B)	1150	1.71	4.0	1.66	4.7	1.62	5.4					6
		1250	1.94	4.2	1.89	4.9	1.85	5.5	1.82	6.3	1.75	7.0	
		1400	2.32	4.7	2.25	5.4	2.21	6.0	2.18	6.7	2.12	7.5	
		1550	2.65	5.3	2.60	5.9	2.56	6.7	2.53	7.3	2.49	8.0	
BSW80E	80A (3B)	1000	2.47	5.4	2.39	6.3	2.36	7.0					8
		1150	3.08	6.3	3.00	7.3	2.94	8.2					
		1250	3.49	6.9	3.41	8.0	3.33	9.0	3.29	10.0	3.20	11.2	
		1400	4.04	8.0	3.98	9.1	3.94	10.3	3.90	11.4	3.82	12.7	
BSW100E	100A (4B)	1000	5.08	9.0	5.00	10.5	4.94	12.0					10
		1100	5.77	10.1	5.71	11.6	5.67	13.1					
		1200	6.45	11.2	6.42	12.8	6.37	14.3	6.33	15.9	6.31	17.6	
		1300	7.13	12.2	7.07	14.0	7.03	15.8	6.99	17.5	6.94	19.3	
		1400	7.76	13.4	7.68	15.1	7.63	17.2	7.55	19.0	7.47	21.0	
BSW125E	125A (5B)	850	9.7	14.6	9.6	16.6	9.5	18.7	9.4	20.9	9.3	23.1	12
		950	11.2	16.5	11.1	18.9	11.0	21.3	10.9	23.7	10.8	26.1	
		1050	12.7	18.5	12.6	21.2	12.5	23.7	12.4	26.4	12.3	29.1	
		1150	14.2	20.4	14.1	23.5	14.0	26.2	13.9	29.2	13.8	32.1	
		1250	15.7	22.8	15.6	26.1	15.5	29.3	15.4	32.4	15.3	35.7	
BSW150E	150A (6B)	800	15.0	21.9	14.8	25.3	14.6	29.0	14.4	32.4	14.2	37.0	15
		900	17.6	24.9	17.3	28.8	17.1	32.5	16.9	36.8	16.7	41.1	
		1000	20.0	28.2	19.8	32.1	19.5	36.5	19.3	41.5	19.0	46.2	
		1100	22.6	31.5	22.3	36.0	22.0	41.2	21.7	45.8	21.5	50.9	
		1200	24.9	34.8	24.6	39.9	24.3	45.4	24.0	50.3	23.7	56.0	
BSW200E	200A (8B)	700	24.5	36.3	24.2	42.8	23.9	48.6					20
		800	29.1	41.7	28.7	48.9	28.3	56.2					
		900	34.0	47.9	33.6	56.0	33.2	64.4					
		1000	38.2	53.1	37.7	61.9	37.3	71.1					
		1100	42.5	58.7	42.0	68.8	41.5	78.2					
BSW200DS	200A (8B)	700	23.2	37.4	22.4	43.4	21.7	49.5	21.0	55.7	20.3	61.9	25
		800	27.9	42.7	27.1	49.6	26.4	56.6	25.7	63.6	25.0	70.7	
		900	32.6	48.0	31.8	55.8	31.1	63.7	30.4	71.6	29.7	79.5	
		1000	37.4	53.4	36.6	62.0	35.9	70.7	35.2	80.0	34.5	88.4	
		1100	42.1	58.7	41.3	68.2	40.6	77.8	39.9	87.5	39.2	97.2	
BSW250E	250A (10B)	700	41.5	62.2	41.0	73.0	40.4	83.8					25
		800	49.3	70.8	48.7	82.7	48.0	94.5					
		900	57.5	80.0	56.8	93.0	56.1	106					
		1000	64.7	90.5	63.9	103	63.1	115					
BSW250DS	250A (10B)	700	51.5	79.6	50.0	93.2	48.7	106	47.5	119	46.3	132	30
		800	61.4	91.0	59.9	107	58.6	121	57.4	137	56.2	151	
		900	71.3	102	69.8	120	68.5	137	67.3	153	66.1	170	
		1000	81.2	114	79.7	133	78.4	152	77.2	170	76.0	189	
BSW300S	300A (12B)	700	71.5	103	70.0	120	68.6	136	67.3	152	66.1	169	35
		800	84.3	118	82.8	137	81.4	155	80.1	174	78.9	193	
		900	97.2	133	95.7	154	94.3	175	93.0	196	91.8	217	

※冷却水は60kPaを超える場合に必要です。