


BE-H 型 (乾式真空ブロワ)



性能表

型 式	吸込口径	回転速度 min ⁻¹	吸込状態空気量 (m ³ /min) および所要動力 (kW)									
			-10kPa (-75mmHg) (-1020mmAq)		-20kPa (-150mmHg) (-2040mmAq)		-30kPa (-225mmHg) (-3060mmAq)		-40kPa (-300mmHg) (-4080mmAq)		-50kPa (-375mmHg) (-5100mmAq)	
			m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW	m ³ /min	kW
BE65H	65A (2½B)	2100	2.54	0.9	2.44	1.4	2.33	1.9	2.21	2.4	2.08	2.9
		2350	2.89	1.0	2.79	1.6	2.68	2.1	2.56	2.7	2.43	3.2
		2450	3.03	1.1	2.93	1.6	2.82	2.2	2.70	2.8	2.57	3.4
		2600	3.24	1.1	3.14	1.7	3.03	2.3	2.91	2.9	2.78	3.6
		2750	3.45	1.2	3.35	1.8	3.24	2.5	3.12	3.1	2.99	3.8
		2900	3.66	1.3	3.56	1.9	3.45	2.6	3.33	3.3	3.20	4.0
		3250	4.15	1.4	4.05	2.2	3.94	2.9	3.82	3.7	3.69	4.4
BE80H	80A (3B)	2100	4.17	1.3	4.04	2.1	3.90	2.9	3.75	3.6	3.59	4.4
		2350	4.61	1.5	4.48	2.4	4.34	3.2	4.19	4.1	4.03	4.9
		2450	4.83	1.6	4.70	2.5	4.56	3.4	4.41	4.3	4.25	5.2
		2600	5.16	1.7	5.03	2.6	4.89	3.6	4.74	4.5	4.58	5.5
		2750	5.49	1.7	5.36	2.8	5.22	3.8	5.07	4.8	4.91	5.8
		2900	5.82	1.8	5.69	2.9	5.55	4.0	5.40	5.0	5.24	6.1
		3250	6.59	2.1	6.46	3.3	6.32	4.5	6.17	5.6	6.01	6.8
BE100H	100A (4B)	2050	5.96	2.1	5.79	3.2	5.61	4.3	5.42	5.4	5.22	6.6
		2150	6.28	2.2	6.11	3.3	5.93	4.5	5.74	5.7	5.54	6.9
		2300	6.77	2.3	6.60	3.6	6.42	4.8	6.23	6.1	6.03	7.4
		2400	7.09	2.4	6.92	3.7	6.74	5.0	6.55	6.4	6.35	7.7
		2700	8.05	2.7	7.88	4.2	7.70	5.7	7.51	7.2	7.31	8.6
		2900	8.69	2.9	8.52	4.5	8.34	6.1	8.15	7.7	7.95	9.3
		3050	9.17	3.1	9.00	4.7	8.82	6.4	8.63	8.1	8.43	9.8
BE125H	125A (5B)	1750	9.9	2.7	9.5	4.5	9.1	6.4	8.7	8.3	8.2	10.2
		1950	11.1	3.0	10.7	5.0	10.3	7.1	9.9	9.3	9.4	11.4
		2150	12.3	3.3	11.9	5.5	11.5	7.8	11.1	10.2	10.6	12.5
		2400	13.8	3.7	13.4	6.2	13.0	8.8	12.6	11.4	12.1	14.0
		2700	15.6	4.1	15.2	7.0	14.8	9.8	14.4	12.8	13.9	15.7
		2900	16.8	4.4	16.4	7.5	16.0	10.5	15.6	13.7	15.1	16.9
		3050	17.7	4.7	17.3	7.9	16.9	11.2	16.5	14.5	16.0	17.8
BE150H	150A (6B)	1550	18.4	5.4	17.7	8.7	17.1	11.9	16.4	15.1	15.7	18.4
		1700	20.3	5.9	19.6	9.5	19.0	13.0	18.3	16.6	17.6	20.2
		1800	21.6	6.3	20.9	10.1	20.3	13.8	19.6	17.6	18.9	21.4
		1950	23.5	6.8	22.8	10.9	22.2	15.0	21.5	19.1	20.8	23.2
		2100	25.4	7.4	24.7	11.8	24.1	16.2	23.4	20.6	22.7	25.0
		2250	27.4	7.8	26.7	12.6	26.1	17.3	25.4	22.0	24.7	26.7
		2550	31.2	8.9	30.5	14.3	29.9	19.6	29.2	24.9	28.5	30.3
BE200H	200A (8B)	1450	33.8	9.7	33.2	15.9	32.6	22.1	31.9	28.2	31.3	34.4
		1550	36.4	10.4	35.8	17.0	35.2	23.6	34.5	30.2	33.9	36.8
		1700	40.2	11.4	39.6	18.6	39.0	25.9	38.3	33.1	37.7	40.3
		1800	42.8	12.0	42.2	19.7	41.6	27.4	40.9	35.1	40.3	42.7
		1950	46.6	13.0	46.0	21.4	45.4	29.7	44.7	38.0	44.1	46.3
		2050	49.2	13.7	48.6	22.5	48.0	31.2	47.3	39.9	46.7	48.6
		2150	51.7	14.4	51.1	23.6	50.0	32.7	49.8	41.8	49.2	51.0
BE250H	250A (10B)	1250	56.7	13.6	55.1	23.5	53.5	33.2	51.9	42.9	50.4	52.6
		1350	61.3	14.8	59.7	25.3	58.1	35.8	56.5	46.3	55.0	56.8
		1450	65.9	15.9	64.3	27.2	62.7	38.5	61.1	49.8	59.6	61.1
		1600	72.9	17.5	71.3	30.0	69.7	42.4	68.1	54.9	66.6	67.4
		1700	77.5	18.6	75.9	31.9	74.3	45.1	72.7	58.4	71.2	71.6
		1800	82.1	19.7	80.5	33.7	78.9	47.7	77.3	61.8	75.8	75.8
		1950	89.1	21.3	87.5	36.5	85.9	51.7	84.3	66.9	82.8	82.1
BE300H	300A (12B)	1300	78.5	20.3	77.5	35.4	76.5	50.6	75.5	65.7	74.5	81.0
		1350	81.8	21.1	80.8	36.8	79.8	52.5	78.8	68.2	77.8	84.1
		1450	88.3	22.6	87.3	39.5	86.3	56.4	85.3	73.3	84.3	90.3
		1550	94.9	24.2	93.9	42.3	92.9	60.3	91.9	78.4	90.9	96.3
		1650	101	25.7	100	45.0	99.0	64.2	98.0	83.4	97.0	103
		1750	108	27.3	107	47.7	106	68.1	105	88.5	104	109
		1200	112	25.1	109	45.7	106	66.3	103	87.0	※101	※97.3
BE350H	350A (14B)	1300	122	27.6	119	50.2	116	72.8	113	95.4	※111	※107
		1350	127	28.9	124	52.5	121	76.1	118	99.7	※116	※112
		1450	137	31.5	134	57.0	131	82.5	128	108	※126	※121
		1550	147	34.0	144	61.5	141	89.0	138	117	※136	※130
		1650	157	36.6	154	66.1	151	95.6	148	125	※146	※140
		900	162	39.0	160	70.0	157	101	154	132	※152	※148
BE400H	400A (16B)	1050	192	45.5	190	81.5	187	118	184	154	※182	※172
		1150	212	50.0	210	89.5	207	129	204	169	※202	※188
		1250	231	54.5	229	97.3	226	140	223	183	※221	※204
		1300	241	57.0	239	101	236	146	233	190	※231	※212
		1350	251	59.5	249	106	246	152	243	198	※241	※221

※BE350H, 400H の最高使用圧力は、-45kPa (-338mmHg) です。性能表は -45kPa 時を示しています。
※放出サイレンサを付ける場合は、サイレンサ圧損を考慮してモータ出力を選定して下さい。

部は、ハウジング、ギヤカバー-水冷式 (冷却水量 15~25L/min)