

BH-T型 (湿式真空ブロワ)



性能表

型 式	吸込 口径	回転速度	吸込状態空気量 (m³/min) および所要動力 (kW)												封水量 ℓ/min
			－20kPa (－150mmHg) (－2040mmAq)		－30kPa (－225mmHg) (－3060mmAq)		－40kPa (－300mmHg) (－4080mmAq)		－50kPa (－375mmHg) (－5100mmAq)		－60kPa (－450mmHg) (－6120mmAq)		－70kPa (－525mmHg) (－7140mmAq)		
		min ⁻¹	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	m³/min	kW	
BH80T	80A (3B)	1150	3.34	2.0	3.20	2.6	2.96	3.4	2.67	4.1	2.23	4.8	1.61	5.5	5
		1250	3.70	2.1	3.56	2.9	3.32	3.7	3.03	4.4	2.59	5.2	1.97	6.0	
		1400	4.24	2.4	4.10	3.2	3.86	4.1	3.57	4.9	3.13	5.8	2.51	6.7	
		1550	4.78	2.6	4.64	3.6	4.40	4.6	4.11	5.5	3.67	6.5	3.05	7.4	
		1700	5.32	2.9	5.18	3.9	4.94	5.0	4.65	6.0	4.21	7.1	3.59	8.1	
BH100T	100A (4B)	1300	5.37	3.1	5.16	4.3	4.84	5.3	4.45	6.5	3.67	7.6	2.70	8.7	6
		1450	6.12	3.5	5.91	4.8	5.59	5.9	5.20	7.2	4.42	8.5	3.45	9.7	
		1550	6.63	3.7	6.42	5.1	6.10	6.4	5.71	7.7	4.93	9.1	3.96	10.3	
		1750	7.63	4.2	7.42	5.7	7.10	7.2	6.71	8.7	5.93	10.2	4.96	11.7	
		1950	8.63	4.7	8.42	6.4	8.10	8.0	7.71	9.7	6.93	11.4	5.96	13.0	
BH125T	125A (5B)	1300	8.5	4.3	8.2	6.1	7.8	7.9	7.3	9.6	6.4	11.3	5.1	13.1	8
		1450	9.6	4.8	9.3	6.8	8.9	8.8	8.4	10.7	7.5	12.6	6.2	14.6	
		1550	10.4	5.2	10.1	7.2	9.7	9.4	9.2	11.4	8.3	13.5	7.0	15.7	
		1750	12.0	5.8	11.7	8.2	11.3	10.6	10.8	12.9	9.9	15.3	8.6	17.7	
		1950	13.5	6.5	13.2	9.1	12.8	11.8	12.3	14.4	11.4	17.0	10.1	19.7	
BH125AT	125A (5B)	1300	11.9	5.6	11.6	8.0	11.2	10.5	10.6	12.9	9.70	15.5	8.00	18.0	8
		1450	13.4	6.2	13.1	8.9	12.7	11.7	12.1	14.4	11.2	17.2	9.50	20.1	
		1550	14.4	6.6	14.1	9.6	13.7	12.5	13.1	15.4	12.2	18.4	10.5	21.4	
		1750	16.5	7.5	16.2	10.8	15.8	14.1	15.2	17.4	14.3	20.8	12.6	24.2	
		1950	18.6	8.4	18.3	12.0	17.9	15.7	17.3	19.4	16.4	23.2	14.7	27.0	
BH150T	150A (6B)	1050	18.1	8.1	17.8	11.4	17.3	14.7	16.6	18.0	15.5	21.3	13.8	24.7	10
		1150	19.9	8.8	19.6	12.5	19.1	16.1	18.4	19.7	17.3	23.4	15.6	27.0	
		1250	21.8	9.6	21.5	13.5	21.0	17.5	20.3	21.5	19.2	25.4	17.5	29.4	
		1400	24.5	10.7	24.2	15.2	23.7	19.6	23.0	24.0	21.9	28.5	20.2	32.9	
		1550	27.3	11.9	27.0	16.8	26.5	21.7	25.8	26.6	24.7	31.5	23.0	36.4	
BH150AT	150A (6B)	1150	27.1	15.7	25.6	20.3	24.0	25.0	21.7	29.9	18.5	34.7	13.6	39.4	12
		1250	29.7	16.9	28.2	22.1	26.6	27.2	24.3	32.4	21.1	37.7	16.2	42.8	
		1400	33.5	19.0	32.0	24.7	30.4	30.4	28.1	36.3	24.9	42.2	20.0	48.0	
		1550	37.4	20.8	35.9	27.3	34.3	33.7	32.0	40.3	28.8	46.7	23.9	53.1	
BH200T	200A (8B)	1150	31.8	14.0	31.1	19.8	30.1	25.7	28.9	31.6	27.0	37.8	24.5	44.3	12
		1250	34.8	15.3	34.1	21.6	33.1	27.9	31.9	34.4	30.0	41.1	27.5	48.1	
		1350	37.8	16.5	37.1	23.3	36.1	30.2	34.9	37.1	33.0	44.4	30.5	52.0	
		1450	40.8	17.7	40.1	25.0	39.1	32.4	37.9	39.9	36.0	47.7	33.5	55.8	
BH200AT	200A (8B)	1150	42.7	24.1	40.4	31.4	38.1	38.7	35.1	47.5	30.7	55.8	25.1	64.1	15
		1250	46.7	26.1	44.4	34.1	42.1	42.1	39.1	51.6	34.7	60.6	29.0	69.7	
		1350	50.6	28.3	48.3	36.8	46.0	45.4	43.0	55.7	38.6	65.5	33.0	75.2	
		1450	54.6	30.2	52.3	39.5	50.0	48.8	47.0	59.8	42.6	70.3	36.9	80.8	
BH250T	250A (10B)	1000	49.3	21.5	47.9	30.4	46.5	39.2	45.0	48.1	43.4	56.9	41.4	65.8	15
		1100	54.4	23.7	53.0	33.4	51.6	43.2	50.1	52.9	48.5	62.6	46.5	72.3	
		1200	59.4	25.8	58.0	36.5	56.6	47.1	55.1	57.7	53.5	68.3	51.5	78.9	
		1300	64.5	28.0	63.1	39.5	61.7	51.0	60.2	62.5	58.6	74.0	56.6	85.5	
BH250AT	250A (10B)	1000	64.3	37.9	62.8	47.9	61.4	57.9	59.6	69.2	56.9	80.2	53.6	90.8	20
		1100	70.9	41.9	69.4	52.7	68.0	63.6	66.2	76.1	63.5	88.2	60.2	99.8	
		1200	77.5	45.7	76.0	57.5	74.6	69.4	72.8	83.1	70.1	96.2	66.7	109	
		1300	84.1	49.5	82.6	62.3	81.2	75.2	79.4	90.0	76.7	104	73.3	118	
BH300T	300A (12B)	1000	74.5	32.0	73.5	45.3	71.5	58.7	68.5	72.0	64.5	85.3	59.5	98.7	25
		1200	89.9	38.4	88.9	54.4	86.9	70.4	83.9	86.4	79.9	102	74.9	118	
		1400	105	44.8	104	63.5	102	82.1	99.0	101	95.0	119	90.0	138	
		1500	113	48.0	112	68.0	110	88.0	107	108	103	128	98.0	148	
BH350T	350A (14B)	900	112	51.0	108	72.0	104	92.3	99.0	113	93.0	134	86.0	154	30
		1000	125	56.7	121	80.0	117	103	112	126	106	149	99.0	172	
		1100	138	62.3	134	88.0	130	113	125	138	119	164	112	189	
		1200	151	68.0	147	96.0	143	123	138	151	132	179	125	206	

※放出サイレンサを付ける場合はサイレンサ圧損を考慮してモータ出力を選定して下さい。